

## XENARC NIGHT BREAKER 220



Up to 220% more brightness<sup>1)1)</sup>  
Compared to minimum ECE R98/R99 requirements.

照射距离更远，驾驶人员可以反应更迅速，与最低法律标准相比



长达250 m的远光

具有更高能见度



Up to 20% whiter light<sup>1)1)</sup> Compared to minimum ECE R98/R99 requirements.

时尚外观，与最低法律标准相比



### 欧司朗功率最强的氙气灯

XENARC NIGHT BREAKER 220 is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER 220 - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

## 产品系列数据表

### 技术参数

产品描述	电参数					光度数据
	功率输入	标称电压	标称功率	输入功率容许偏差	测试电压	光通量
XENARC NIGHT BREAKER 220 D1S	35 W	85 V	35 W	±3 %	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D2S	35 W	85 V	35 W	±3 %	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D3S	35 W	42 V	35 W	±3 %	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D4S	35 W	42 V	35 W	±3 %	13.5 V	3200 lm

产品描述	Physical Attributes & Dimensions			寿命
	灯头 (标准名称)	长度	直径	Lifespan B3
XENARC NIGHT BREAKER 220 D1S	PK32d-2	77.3 mm	9 mm	1500 hr
XENARC NIGHT BREAKER 220 D2S	P32d-2	77.3 mm	9 mm	1500 hr
XENARC NIGHT BREAKER 220 D3S	PK32d-5	77.3 mm	9 mm	2000 hr
XENARC NIGHT BREAKER 220 D4S	P32d-5	77.3 mm	9 mm	2000 hr

产品描述	使用寿命 Tc	认证与标准 ECE 分类	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
			Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
XENARC NIGHT BREAKER 220 D1S	3000 hr	D1S <sup>1)</sup>	4062172398619   4062172397735	Lead	7439-92-1
XENARC NIGHT BREAKER 220 D2S	3000 hr	D2S <sup>1)</sup>	4062172398640   4062172397766		
XENARC NIGHT BREAKER 220 D3S	3000 hr	D3S <sup>1)</sup>	4062172398671   4062172397797	Lead	7439-92-1
XENARC NIGHT BREAKER 220 D4S	3000 hr	D4S <sup>1)</sup>	4062172398701   4062172397827		







产品描述	Safe Use Instruction	Declaration No. in SCIP database
XENARC NIGHT BREAKER 220 D1S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0682beb0-fcb6-4643-b1bf-f0df283c2352   5a5302eb-4799-4cbd-a466-1a125eac6e0a
XENARC NIGHT BREAKER 220 D2S		In work
XENARC NIGHT BREAKER 220 D3S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2322ca85-73dd-494d-97a0-7d1ae5c23717   3dea30b6-ada1-419d-b9db-7582b1c7f8bf
XENARC NIGHT BREAKER 220 D4S		In work

## 产品系列数据表

<sup>1)</sup> 仅可使用经过认证的电子控制装置运行

## 产品系列数据表

### 下载数据

文件	
	User instruction GPRS_Safety symbols instructions
	Addon Technical Information Product Certificates HID
	ref_pim_amsproduct360degreeimages XENARC ORIGINAL D1S 66140
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D2S 66240XNB
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D3S 66340XNB
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D4S 66440XNB

#### 安全建议

XENARC lamps should be replaced by a qualified mechanicThis product must only be operated with approved electronic control gear

#### 法律建议

Light output compared to the minimum ECE R112/R37 requirementsThis product must only be operated with approved electronic control gearXENARC lamps should be replaced by a qualified mechanicReduced UV emission | For projection headlights | ECE approval and DOT label± 450 lm

#### 应用建议

更多详细应用信息和图形,请参阅产品数据表。

#### 免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。